



LORO-X BALCONY DRAINS, SERIES F, SINGLE-PART UNITS, VERTICAL SOCKET, WITHOUT THERMAL INSULATION DN 50

LORO-X balcony drain vertical one-piece without insulation with height adjustment DN 50

Opis

LORO-X balcony drain, series F, one-piece, without thermal insulation, vertical outlet, with pre-fitted connecting collar made of bitumen/EPDM composite, according to DIN EN 1253 with raised quality standard, made of steel, hot-dip galvanized, with long-life coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, consisting of drain pot, connecting collar, clamping ring, drainage ring, holding fixture for strainer 100 x 100 mm (for installation height 35 - 150 mm), stainless steel strainer DN50



Podatki o izdelku

EAN koda	4038088007815
ETIM razred	EC004949
Nazivni premer	DN 50
Zunanje mere (VxŠxD)	230 x 230 x 404 mm
Teža	2,20 Kg (STK)
Skupina izdelkov	4
Carinska tarifna številka	73089098
Material / Barva	Stahl feuerverzinkt, Silber

Opomba za uporabo

Die Serien E und F beinhalten Balkonabläufe als Einzelabläufe mit Anschlussmanschette. Serie F beinhaltet Einzelabläufe mit Anschlussmanschette mit höhenverstellbarer Siebaufnahme und Endsieb aus Edelstahl. Im Standard werden die Serien E und F aus feuerverzinktem Stahl mit zusätzlicher Beschichtung gefertigt. Auf Anfrage ist auch die Fertigung aus massivem Kupfer möglich. Einsatzgebiete Balkone mit Abdichtungsbahnen, Fliesen- oder Plattenbelag.

Prenosi



Alles online

[Navodila za vgradnjo \(PDF\)](#)
[Certifikat \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[BIM 3D \(IFC\)](#)

[Merska risba \(PDF\)](#)
[Aufbauschema \(PDF\)](#)
[CAD 3D \(DWG\)](#)

[Prospekt \(PDF\)](#)
[Podatkovni list sistema LX 962](#)
[BIM 3D \(STEP\)](#)