



LORO-X BALKONABL.F.BRANDSCHUTZ,SENKR.2TL

LORO-X balcony drain for fire protection vertical two-piece with height adjustment series F DN 70

Beschrijving

LORO-X balcony drain, fire protection system, series F, general building authority test certificate no. P-MPA-E-09-010, two-piece, with thermal insulation, vertical outlet, with pre-fitted connecting collar made of bitumen/EPDM composite, according to DIN EN 1253 with raised quality standard, made of steel, hot-dip galvanized, with long-life coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, consisting of drain pot, connecting collar, clamping ring, sealing element, extension cartridge (for installation height 40 - 120 mm), connecting collar, clamping ring, drainage ring, holding fixture for strainer 100 x 100 mm (for installation height 35 - 150 mm), stainless steel strainer, DN70



Artikelgegevens

EAN-code	4038088096307
ETIM Klasse	EC011398
Nominale diameter	DN 70
Gewicht	5,60 Kg (STK)
Productgroep	4
Douanetariefnr	73089098
r	
Materiaal / Kleur	Stahl feuerverzinkt, Silber

Gebruiksaanwijzing

Die Serien E und F beinhalten Balkonabläufe als Einzelabläufe mit Anschlussmanschette. Serie F beinhaltet Einzelabläufe mit Anschlussmanschette mit höhenverstellbarer Siebaufnahme und Endsieb aus Edelstahl.

Downloads



Alles online

[Installatiehandleiding \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[Maattekening \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)