

# LORO-X BALCONY DRAINS, SERIES F, SINGLE-PART UNIT, HORIZONTAL SOCKET, WITHOUT THERMAL INSULATION DN 70

**LORO-X balcony drain 3 degrees one-piece without insulation with height adjustment DN 70**

## Voce di capitolato

LORO-X balcony drain, series F, one-piece, without thermal insulation, lateral outlet 3 degrees, with pre-fitted connecting collar made of bitumen/EPDM composite, according to DIN EN 1253 with raised quality standard, made of steel, hot-dip galvanized, with long-life coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, consisting of drain pot, connecting collar, clamping ring, drainage ring, holding fixture for strainer 100 x 100 mm (for installation height 35 - 150 mm), stainless steel strainer DN70





## Dati articolo

| | |
|---|---|
| Codice EAN | **4038088008164** |
| Classe ETIM | **EC004949** |
| Diametro nominale | **DN 70** |
| Misure esterne (AxLxP) | **230 x 367 x 270 mm** |
| Peso | **2,70 Kg (STK)** |
| Gruppo prodotti | **4** |
| Numero tariffa doganale | **73089098** |
| Materiale / Colore | **Stahl feuerverzinkt, Silber** |

## Note d'uso

Die Serien E und F beinhalten Balkonabläufe als Einzelabläufe mit Anschlussmanschette. Serie F beinhaltet Einzelabläufe mit Anschlussmanschette mit höhenverstellbarer Siebaufnahme und Endsieb aus Edelstahl.. Im Standard werden die Serien E und F aus feuerverzinktem Stahl mit zusätzlicher Beschichtung gefertigt. Auf Anfrage ist auch die Fertigung aus massivem Kupfer möglich.Einsatzgebiete Balkone mit Abdichtungsbahnen, Fliesen- oder Plattenbelag.

## Download

Alles online

Istruzioni di installazione (PDF)
Certificato (PDF)
CAD 2D (DXF)
BIM 3D (IFC)
Disegno dimensionale (PDF)
Aufbauschema (PDF)
CAD 3D (DWG)
Brochure (PDF)
Scheda tecnica del sistema LX 968
BIM 3D (STEP)