


LORO-X BALCONY DRAINS, SERIES F, SINGLE-PART UNIT, HORIZONTAL SOCKET, WITHOUT THERMAL INSULATION DN 70

LORO-X balcony drain 3 degrees one-piece without insulation with height adjustment DN 70

Descripción

LORO-X balcony drain, series F, one-piece, without thermal insulation, lateral outlet 3 degrees, with pre-fitted connecting collar made of bitumen/EPDM composite, according to DIN EN 1253 with raised quality standard, made of steel, hot-dip galvanized, with long-life coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, consisting of drain pot, connecting collar, clamping ring, drainage ring, holding fixture for strainer 100 x 100 mm (for installation height 35 - 150 mm), stainless steel strainer DN70




Datos del artículo

Código EAN	4038088008164
Clase ETIM	EC004949
Diámetro nominal	DN 70
Medidas exteriores (AxAxL)	230 x 367 x 270 mm
Peso	2,70 Kg (STK)
Grupo de productos	4
Número de arancel aduanero	73089098
Material / Color	Stahl feuerverzinkt, Silber

Nota de uso

Die Serien E und F beinhalten Balkonabläufe als Einzelabläufe mit Anschlussmanschette. Serie F beinhaltet Einzelabläufe mit Anschlussmanschette mit höhenverstellbarer Siebaufnahme und Endsieb aus Edelstahl.. Im Standard werden die Serien E und F aus feuerverzinktem Stahl mit zusätzlicher Beschichtung gefertigt. Auf Anfrage ist auch die Fertigung aus massivem Kupfer möglich. Einsatzgebiete Balkone mit Abdichtungsbahnen, Fliesen- oder Plattenbelag.



Descargas



Alles online

[Instrucciones de instalación \(PDF\)](#)

Certificado (PDF)

CAD 2D (DXF)

BIM 3D (IFC)

[Dibujo dimensional \(PDF\)](#)

[Aufbauschema \(PDF\)](#)

CAD 3D (DWG)

[Folleto \(PDF\)](#)

Ficha técnica del sistema LX 968

BIM 3D (STEP)