LORO-X FLACHDACHABL.A.STAHL VERZ.,F.FLÜS

LORO-X Galvanised steel flat roof drain for liquid plastic DN 80

Beskrivelse

LORO-X flat roof renovation drain, one-piece, without thermal insulation, vertical outlet, for main drainage with gravity flow, discharge rate 5.6 l/s at 35 mm water level on the roof, with bonding flange for liquid plastic, with transition sealing element for pipe internal diameter 98-106 mm, according to DIN EN 1253 with raised quality standard, proof of performance with standard-compliant testing system with 4.2 m non-ventilated downpipe, made of steel, hot-dip galvanized, DN 80



Artikeldata

EAN-kode	**4038088077955**
ETIM Klasse	**EC011398**
Nominel diameter	**DN 80**
Ydermål (HxBxL)	**370 x 370 x 494 mm**
Vægt	**7,00 Kg (STK)**
Produktgruppe	**4**
Toldtarifnummer	**73089098**
Materiale / Farve	**Stahl feuerverzinkt, Silber**

Brugsanvisning

LORO-Flachdach-Sanierungsablauf mit Klebeflansch für Flüssigkunststoff DN 80 mit übergangs-Dichtelement für Rohr-Innendurchmesser 98 - 106 mm

Downloads

Alles online

Installationsvejledning (PDF)
Certifikat (PDF)
Måltegning (PDF)
CAD 2D (DXF)
Brochure (PDF)
CAD (DWG)