


LORO-X FLACHDACHABL.A.STAHL VERZ.,F.FLÜS

LORO-X Galvanised steel flat roof drain for liquid plastic DN 80

Descripción

LORO-X flat roof renovation drain, one-piece, without thermal insulation, vertical outlet, for main drainage with gravity flow, discharge rate 5.6 l/s at 35 mm water level on the roof, with bonding flange for liquid plastic, with transition sealing element for pipe internal diameter 98-106 mm, according to DIN EN 1253 with raised quality standard, proof of performance with standard-compliant testing system with 4.2 m non-ventilated downpipe, made of steel, hot-dip galvanized, DN 80



Datos del artículo

Código EAN	4038088077955
Clase ETIM	EC011398
Diámetro nominal	DN 80
Medidas exteriores (AxAxL)	370 x 370 x 494 mm
Peso	7,00 Kg (STK)
Grupo de productos	4
Número de arancel aduanero	73089098
Material / Color	Stahl feuerverzinkt, Silber

Nota de uso

LORO-Flachdach-Sanierungsablauf mit Klebeflansch für Flüssigkunststoff DN 80 mit Übergangs-Dichtelement für Rohr-Innendurchmesser 98 - 106 mm

Descargas



Alles online

[Instrucciones de instalación \(PDF\)](#)

[Certificado \(PDF\)](#)

[Dibujo dimensional \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Folleto \(PDF\)](#)

[CAD \(DWG\)](#)