


**LORO-X BALCONY DRAINS, SERIES E, TWO-PART UNIT, HORIZONTAL
SOCKET, WITH THERMAL INSULATION DN 70**

LORO-X balcony drain 3 degrees two-piece with heat insulation DN 70

Opis

LORO-X balcony drain, series E, two-piece, with thermal insulation, lateral outlet 3 degrees, with pre-fitted connecting collar made of bitumen/EPDM composite, according to DIN EN 1253 with raised quality standard, made of steel, hot-dip galvanized, with long-life coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, consisting of drain pot, connecting collar, clamping ring, sealing element, extension cartridge (for installation height 40 - 120 mm), connecting collar, clamping ring, drainage ring, round strainer, DN70



Podaci o artiklu

EAN kod	4038088008430
ETIM klasa	EC004949
Nazivni promjer	DN 70
Vanjske mjere (VxŠxD)	230 x 367 x 273 mm
Težina	4,60 Kg (STK)
Grupa proizvoda	4
Carinski tarifni broj	73089098
Materijal / Boja	Stahl feuerverzinkt, Silber

Napomena za upotrebu

Die Serien E und F beinhalten Balkonabläufe als Einzelabläufe mit Anschlussmanschette. Serie E beinhaltet Einzelabläufe mit Anschlussmanschette mit Endsieb aus Kunststoff. Im Standard werden die Serien E und F aus feuerverzinktem Stahl mit zusätzlicher Beschichtung gefertigt. Auf Anfrage ist auch die Fertigung aus massivem Kupfer möglich. Einsatzgebiete Balkone mit Abdichtungsbahnen, Fliesen- oder Plattenbelag.

Preuzimanja



Alles online

[Upute za ugradnju \(PDF\)](#)

Certifikat (PDF)

CAD 2D (DXF)

BIM 3D (IFC)

[Dimenzijski crtež \(PDF\)](#)

[Aufbauschema \(PDF\)](#)

CAD 3D (DWG)

[Prospekt \(PDF\)](#)

Tehnički list sustava LX 945

BIM 3D (STEP)