

LORO-X SINGLE DRAIN TYPE A, STRAIGHT RUN-OFF

LORO-X single drain with vertical rim DN 50

Beskrivelse

LORO-X balcony drain, series A with supporting edge, one-piece, without thermal insulation, vertical outlet, according to DIN EN 1253 with raised quality standard, made of steel, hot-dip galvanized, with long-life coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, consisting of: consisting of drain pot (clamping ring width 35 mm circumferential), sealing element, plastic strainer 82 x 82 mm (for installation height approx. 30 +/- 5 mm), DN50




Artikkeldata

EAN-kode	4038088008577
ETIM-klasse	EC011398
Nominell diameter	DN 50
Utvendige mål (HxBxL)	201 x 201 x 275 mm
Vekt	1,10 Kg (STK)
Produktgruppe	4
Tolltariffnummer	73089098
Materiale / Farge	Stahl feuerverzinkt, Silber

Bruksanvisning

Serie A beinhaltet Einzelabläufe mit Stützrand aus Stahl mit Endsieb, beinhaltet Einzelabläufe mit Stützrand aus Stahl mit höhenverstellbarer Siebaufnahme und Endsieb aus Edelstahl. Beide Serien weisen Öffnungen für Sickerwasser oberhalb des stützrandes auf, sodass Restwasserbildung vermieden wird. Einsatzgebiete Balkone ohne Abdichtungsbahnen mit Gussasphalt, Fertiggestrich oder Fliesenbelag im Mörtelbett.



Nedlasteringer



Alles online

[Monteringsanvisning \(PDF\)](#)

[Godkjenning \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Måltgning \(PDF\)](#)

[Aufbauschema \(PDF\)](#)

[CAD \(DWG\)](#)

[Brosjyre \(PDF\)](#)

[Systemdatablad LX 919](#)