

LORO-X SINGLE DRAIN TYPE A, STRAIGHT RUN-OFF

LORO-X single outlet with support edge 35 mm

Beskrivning

LORO-X balcony drain, series A with supporting edge, one-piece, without thermal insulation, vertical outlet, according to DIN EN 1253 with raised quality standard, made of steel, hot-dip galvanized, with long-life coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, consisting of: consisting of drain pot (clamping ring width 35 mm circumferential), sealing element, plastic strainer 82 x 82 mm (for installation height approx. 30 +/- 5 mm), DN70




Artikeldata

EAN-kod	4038088008584
ETIM-klass	EC011398
Nominell diameter	DN 70
Vikt	1,30 Kg (STK)
Produktgrupp	4
Tullnummer	73089098
Material / Färg	Stahl feuerverzinkt, Silber

Användningsanvisning

Serie A beinhaltet Einzelabläufe mit Stützrand aus Stahl mit Endsieb. Beide Serien weisen Öffnungen für Sickerwasser oberhalb des Stützrandes auf, sodass Restwasserbildung vermieden wird. Einsatzgebiete Balkone ohne Abdichtungsbahnen mit Gussasphalt, Fertigestrich oder Fliesenbelag im Mörtelbett.



Nedladdningar



Alles online

[Måttavering \(PDF\)](#)

[CAD \(DWG\)](#)

[Broschyr \(PDF\)](#)

[CAD 2D \(DXF\)](#)