


LORO-X SINGLE DRAIN TYPE A, WITH LATERAL RUN-OFF

LORO-X single drain with 3-degree support rim DN 50

Leírás

LORO-X balcony drain, series A with supporting edge, one-piece, without thermal insulation, lateral outlet 3 degrees, according to DIN EN 1253 with raised quality standard, made of steel, hot-dip galvanized, with long-life coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, consisting of: consisting of drain pot (clamping ring width 35 mm circumferential), sealing element, plastic strainer 82 x 82 mm (for installation height approx. 30 +/- 5 mm), DN50



Cikkadatok

EAN kód	4038088008744
ETIM osztály	EC011398
Névleges átmérő	DN 50
Külső méretek (MxSzxH)	201 x 352 x 102 mm
Súly	1,20 Kg (STK)
Termékcsoport	4
Vámtarifaszám	73089098
Anyag / Szín	Stahl feuerverzinkt, Silber

Használati megjegyzés

Serie A beinhaltet Einzelabläufe mit Stützrand aus Stahl mit Endsieb, beinhaltet Einzelabläufe mit Stützrand aus Stahl mit höhenverstellbarer Siebaufnahme und Endsieb aus Edelstahl. Beide Serien weisen Öffnungen für Sickerwasser oberhalb des Stützrandes auf, sodass Restwasserbildung vermieden wird. Einsatzgebiete Balkone ohne Abdichtungsbahnen mit Gussasphalt, Fertigestrich oder Fliesenbelag im Mörtelbett.

Letöltések



Alles online

[Szerelési útmutató \(PDF\)](#)

[Engedély \(PDF\)](#)

CAD 2D (DXF)

[Mértrajz \(PDF\)](#)

[Aufbauschema \(PDF\)](#)

CAD (DWG)

[Prospektus \(PDF\)](#)

LX rendszer-adatlap 921