


LORO-X SINGLE DRAIN TYPE B, WITH LATERAL RUN-OFF

LORO-X single drain with 3 degree rim with height adjustment DN 50

Opis

LORO-X balcony drain, series B with clamping ring, one-piece, without thermal insulation, lateral outlet 3 degrees, according to DIN EN 1253 with raised quality standard, made of steel, hot-dip galvanized, with long-life coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, consisting of: consisting of drain pot (clamping ring width 35 mm circumferential), sealing element, holding fixture for strainer 100 x 100 mm (for installation height 35 - 140 mm), stainless steel strainer, DN50




Podaci o artiklu

EAN kod	4038088008775
ETIM klasa	EC011398
Nazivni promjer	DN 50
Vanjske mjere (VxŠxD)	201 x 352 x 207 mm
Težina	1,40 Kg (STK)
Grupa proizvoda	4
Carinski tarifni broj	73089098
Materijal / Boja	Stahl feuerverzinkt, Silber

Napomena za upotrebu

Serie B beinhaltet Einzelabläufe mit Stützrand aus Stahl mit höhenverstellbarer Siebaufnahme und Endsieb aus Edelstahl, beinhaltet Einzelabläufe mit Stützrand aus Stahl mit höhenverstellbarer Siebaufnahme und Endsieb aus Edelstahl. Beide Serien weisen Öffnungen für Sickerwasser oberhalb des Stützrandes auf, sodass Restwasserbildung vermieden wird. Einsatzgebiete Balkone ohne Abdichtungsbahnen mit Gussasphalt, Fertigestrich oder Fliesenbelag im Mörtelbett.



Preuzimanja



Alles online

[Upute za ugradnju \(PDF\)](#)

Certifikat (PDF)

CAD 2D (DXF)

BIM 3D (IFC)

[Dimenzijski crtež \(PDF\)](#)

[Aufbauschema \(PDF\)](#)

CAD 3D (DWG)

[Prospekt \(PDF\)](#)

Tehnički list sustava LX 925

BIM 3D (STEP)