

LORO-X BALK.-DI.3GR.F.O.BALK.O.WD DN 70

LORO-X Balcony Direct 3 degrees for upper balconies without thermal insulation DN 70

Kuvaus

LORO direct balcony drain with connecting collar made of bitumen/EPDM composite, series H, according to DIN EN 1253 with raised quality standard, made of steel, hot-dip galvanized, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, lateral outlet, without thermal insulation, one-piece, consisting of drain pot, connecting collar, clamping ring, drainage ring, holding fixture for strainer (for installation height 35 - 155 mm), end strainer for upper balconies, DN70




Tuotetiedot

EAN-koodi	4038088068687
ETIM-luokka	EC011398
Nimellishalkaisija	DN 70
Ulkomitat (KxLxS)	275 x 389 x 287 mm
Paino	3,80 Kg (STK)
Tuoteryhmä	4
Tullitariffin numero	73089098
Materiaali / Väri	Stahl feuerverzinkt, Silber

Käyttöohje

kein Verwendungshinweis notwendig



Lataukset



Alles online

[Mittapiirustus \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Esite \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[Hyväksyntä \(PDF\)](#)

[BIM 3D \(STEP\)](#)