



LORO-X BALK.-DI.2-TLF.O.BALK.O.WD DN 70

LORO-X direct balcony drain, two-piece, for upper balconies without thermal insulation DN 70

Popis

LORO direct balcony drain with connecting collar made of bitumen/EPDM composite, series H, according to DIN EN 1253 with raised quality standard, made of steel, hot-dip galvanized, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, lateral outlet, without thermal insulation, two-piece, consisting of drain pot, connecting collar, clamping ring without drainage openings, extension cartridge (for installation height 60 - 120 mm), connecting collar, clamping ring, drainage ring, holding fixture for strainer (for installation height 35-155 mm), end strainer for upper balconies, DN70



Údaje o artiklu

EAN kód	4038088068724
ETIM třída	EC011398
Jmenovitý průměr	DN 70
Hmotnost	5,30 Kg (STK)
Skupina produktů	4
Celní sazebník	73089098
Materiál / Barva	Stahl feuerverzinkt, Silber

Pokyny k použití

kein Verwendungshinweis notwendig

Ke stažení



Alles online

[Výkres rozměrů \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[Prospekt \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)