LORO-X BALKONDIREKTABTL.2TLG.O.WD.SIEB R

LORO-X balcony direct drain, two-piece, without insulation, H series DN 70

Descriere

LORO-X direct balcony drain, series H, two-piece, without thermal insulation, vertical outlet, with pre-fitted connecting collar made of bitumen/EPDM composite, according to DIN EN 1253 with raised quality standard, made of steel, hot-dip galvanized, with long-life coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, consisting of drain pot, connecting collar, clamping ring without drainage openings, extension cartridge (for installation height 60 - 120 mm), connecting collar, clamping ring, drainage ring, holding fixture for strainer (for installation height 35 - 150 mm), strainer for pipe opening for balcony floors, DN70





Date articol

Cod EAN	4038088058589
Clasă ETIM	EC004949
Diametru nominal	DN 70
Dimensiuni exterioare (ÎxLxA)	275 x 275 x 521 mm
Greutate	6,20 Kg (STK)
Grupă de produse	4
Număr tarif vamal	73089098
Material / Culoare	Stahl feuerverzinkt, Silber

Notă de utilizare

Die Serie H beinhaltet Balkonabläufe mit Anschlussmanschette für die Anbindung an Abdichtungsbahnen. Die Anschlussmanschette besteht aus Bitumen/EPDM Verbund (Standard) oder auf Anfrage aus PVC oder ECB und wird werkseitig vormontiert. Im Standard wird die Serie H aus feuerverzinktem Stahl mit zusätzlicher Beschichtung gefertigt. Auf Anfrage ist auch die Fertigung aus massivem Kupfer möglich. Einsatzgebiete Balkone und Terrassen mit Abdichtungsbahnen, Fliesen- oder Plattenbelag. Weitere Einsatzbeispiele finden Sie mit detailierter Beschreibung in unserem Prospekt LORO-X Balkonentwässerung.

Descărcări

Alles online

Instrucțiuni de montaj (PDF)
Certificat (PDF)
CAD 2D (DXF)
BIM 3D (IFC)
Desen CAD (PDF)
Aufbauschema (PDF)
CAD 3D (DWG)
Broșură (PDF)
Fișă tehnică de sistem LX 904
BIM 3D (STEP)