## LORO-X BALKONDIREKTABL.2TLG.O.WD.ENDSIEB

**LORO-X balcony direct drain, two-part without insulation End grating DN 70**

### Описание

LORO-X direct balcony drain, series H, two-piece, without thermal insulation, vertical outlet, with pre-fitted connecting collar made of bitumen/EPDM composite, according to DIN EN 1253 with raised quality standard, made of steel, hot-dip galvanized, with long-life coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, consisting of drain pot, connecting collar, clamping ring without drainage openings, extension cartridge (for installation height 60 - 120 mm), connecting collar, clamping ring, drainage ring, holding fixture for strainer (for installation height 35 - 150 mm), strainer for upper balconies, DN70





### Данни за артикула

| | |
|---|---|
| EAN код | 4038088058626 |
| ETIM клас | EC004949 |
| Номинален диаметър | DN 70 |
| Външни размери (ВхШхД) | 275 x 275 x 521 mm |
| Тегло | 6,20 Kg (STK) |
| Продуктова група | 4 |
| Митнически тарифен номер | 73089098 |
| Материал / Цвят | Stahl feuerverzinkt, Silber |

### Забележка за употреба

Die Serie H beinhaltet Balkonabläufe mit Anschlussmanschette für die Anbindung an Abdichtungsbahnen. Die Anschlussmanschette besteht aus Bitumen/EPDM Verbund (Standard) oder auf Anfrage aus PVC oder ECB und wird werkseitig vormontiert. Im Standard wird die Serie H aus feuerverzinktem Stahl mit zusätzlicher Beschichtung gefertigt. Auf Anfrage ist auch die Fertigung aus massivem Kupfer möglich. Einsatzgebiete Balkone und Terrassen mit Abdichtungsbahnen, Fliesen- oder Plattenbelag. Weitere Einsatzbeispiele finden Sie mit detailierter Beschreibung in unserem Prospekt LORO-X Balkonentwässerung.

### Изтегляния

Alles online

Инструкция за монтаж (PDF)
Сертификат (PDF)
CAD 2D (DXF)
BIM 3D (IFC)
CAD чертеж (PDF)
Aufbauschema (PDF)
CAD 3D (DWG)
Брошура (PDF)
Системен технически лист LX 902
BIM 3D (STEP)