



LORO-X BALK.-DI.2-TLF.BA.GES.M.WD DN 70

LORO-X Balcony Direct Two-Piece for Balcony Floor with Insulation DN 70

Popis

LORO direct balcony drain with connecting collar made of bitumen/EPDM composite, series H, according to DIN EN 1253 with raised quality standard, made of steel, hot-dip galvanized, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, lateral outlet, with thermal insulation, two-piece, consisting of drain pot, connecting collar, clamping ring without drainage openings, extension cartridge (for installation height 60 - 120 mm), connecting collar, clamping ring, drainage ring, holding fixture for strainer (for installation height 35 - 155 mm), round strainer, DN70



Údaje o artikli

EAN kód	4038088068717
ETIM trieda	EC011398
Menovitý priemer	DN 70
Vonkajšie rozmery (VxŠxH)	275 x 389 x 421 mm
Hmotnosť	5,60 Kg (STK)
Skupina produktov	4
Colný sadzobník	73089098
Materiál / Farba	Stahl feuerverzinkt, Silber

Pokyny na použitie

kein Verwendungshinweis notwendig

Na stiahnutie



Alles online

[Rozmerový výkres \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Prospekt \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[Certifikát \(PDF\)](#)

[BIM 3D \(STEP\)](#)