



LORO-X ROHR-WAND-U.DECKENDURCHFUEHRUNG,

LORO-X pipe-wall and ceiling passage DN 100

Описание

LORO-X pipe wall and slab penetration with blocking flange, media-carrying, made of steel, hot-dip galvanized, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, length 400 mm, DN100



Данни за артикула

EAN код	4038088012604
ETIM клас	EC003024
Номинален диаметър	DN 100
Номинална дължина/градус	400
Външни размери (ВxШxД)	330 x 330 x 400 mm
Тегло	3,40 Kg (STK)
Продуктова група	1
Митнически тарифен номер	73089098
Материал / Цвят	Stahl feuerverzinkt, Rotbraun

Забележка за употреба

Gemäß DIN EN 12056-3 7.6.2 sind bei Regenwasserleitungen, die durch Außenwände führen, wasserdichte Rohrdurchführungen zu verwenden. Die Rohrdurchführung mit Sperrflansch eignet sich für wasserundurchlässigen (WU) Beton.

Изтегляния



Alles online

[CAD чертеж \(PDF\)](#)

[CAD \(DWG\)](#)

[Брошура \(PDF\)](#)

[CAD 2D \(DXF\)](#)