

LX-AUFSATZELEMENT M.AUFGEK.KLEBEFL.

LORO-X surface-mounted element with upturned adhesive flange 270 mm long Series V-AK DN 70

Leírás

LORO-X balcony extension unit for two piece version, series V-AK, with upstanded bonding flange for sealing from liquid plastic at wall areas, according to DIN EN 1253 with raised quality standard, made of stainless steel, consisting of: extension body with upstanded bonding flange and sealing element DN100, made of stainless steel, DN70




Cikkadatok

EAN kód	4038088102510
ETIM osztály	EC011398
Névleges átmérő	DN 70
Külső méretek (MxSzxH)	245 x 218 x 366 mm
Súly	2,10 Kg (STK)
Termékcsoport	4
Vámtarifaszám	73072980
Anyag / Szín	Edelstahl, Silber

Használati megjegyzés

LORO-Balkonablauf mit Aufsatzelemente, Serie V-AK für Balkonabdichtung aus Flüssigkunststoffen im Wandbereich. Zweiteilige Ausführung für wärmedämmte Balkone, mit aufgekanteten Klebeflansch für Einbau in Wand- oder Eckbereichen.



Letöltések



Alles online

[Szerelési útmutató \(PDF\)](#)

[Engedély \(PDF\)](#)

LX rendszer-adatlap 1226

CAD 2D (DXF)

BIM 3D (IFC)

[Méretrajz \(PDF\)](#)

[Aufbauschema \(PDF\)](#)

LX rendszer-adatlap 1227

CAD 3D (DWG)

[Prospektus \(PDF\)](#)

LX rendszer-adatlap 1225

LX rendszer-adatlap 1228

BIM 3D (STEP)