

LX-AUFSATZELEMENT M.ECKFL. SR.V-AK DN70

LORO-X add-on element with corner flange 70 mm long Series V-AK DN 70

Popis

LORO-X balcony set up element for one piece version, series V-AK, with upstand bonding flange for sealing from liquid plastic at wall corner areas, according to DIN EN 1253 with raised quality standard, made of stainless steel, consisting of: set up element with upstanding bonding cornerflange and sealing element DN100, made of stainless steel, DN70




Údaje o artiklu

EAN kód	4038088102558
ETIM třída	EC011398
Jmenovitý průměr	DN 70
Vnější rozměry (VxŠxD)	218 x 218 x 166 mm
Hmotnost	1,50 Kg (STK)
Skupina produktů	4
Celní sazebník	73072980
Materiál / Barva	Edelstahl, Silber

Pokyny k použití

LORO-Balkonablauf mit Aufsatzelemente, Serie V-AK für Balkonabdichtung aus Flüssigkunststoffen im Wandbereich.



Ke stažení



Alles online

[Návod k instalaci \(PDF\)](#)

[Certifikát \(PDF\)](#)

[Systémový datový list LX 1226](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Výkres rozměrů \(PDF\)](#)

[Aufbauschema \(PDF\)](#)

[Systémový datový list LX 1227](#)

[CAD 3D \(DWG\)](#)

[Prospekt \(PDF\)](#)

[Systémový datový list LX 1225](#)

[Systémový datový list LX 1228](#)

[BIM 3D \(STEP\)](#)