


LX-AUFSATZELEMENT M.ECKFL.SR.V-AK,270 MM

LORO-X Surface-mounted element with corner flange 270 mm long Series V-AK DN 50

Description

LORO-X balcony extension unit for two piece version, series V-AK, with upstanded bonding flange for sealing from liquid plastic at wall corner areas, according to DIN EN 1253 with raised quality standard, made of stainless steel, consisting of: extension body with upstanded bonding cornerflange and sealing element DN70, made of stainless steel, DN50



Article information

EAN Code	4038088108963
ETIM Class	EC011398
Nominal diameter	DN 50
Outside measurements (HxWxL)	366 x 218 x 218 mm
Weight	2,30 Kg (STK)
Product group	4
Customs tariff number	73072980
Material / Color	Edelstahl, Silber

Usage note

LORO-Balkonablauf mit Aufsatzelemente, Serie V-AK für Balkonabdichtung aus Flüssigkunststoffen im Wandbereich. Zweiteilige Ausführung für wärmegeämmte Balkone, mit aufgekanteten Klebeflansch für Einbau in Wand-oder Eckbereichen.

Downloads



Alles online

[Installation \(PDF\)](#)

[Certificate \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[CAD drawing \(PDF\)](#)

[Aufbauschema \(PDF\)](#)

[Brochure \(PDF\)](#)

[CAD 2D \(DXF\)](#)