


LX-AUFSATZELEMENT M.ECKFL.SR.V-AK,270 MM

LORO-X Surface-mounted element with corner flange 270 mm long Series V-AK DN 50

Beskrivelse

LORO-X balcony extension unit for two piece version, series V-AK, with upstanded bonding flange for sealing from liquid plastic at wall corner areas, according to DIN EN 1253 with raised quality standard, made of stainless steel, consisting of: extension body with upstanded bonding cornerflange and sealing element DN70, made of stainless steel, DN50



Artikkeldata

EAN-kode	4038088108963
ETIM-klasse	EC011398
Nominell diameter	DN 50
Utvendige mål (HxBxL)	366 x 218 x 218 mm
Vekt	2,30 Kg (STK)
Produktgruppe	4
Tolltariffnummer	73072980
Materiale / Farge	Edelstahl, Silber

Bruksanvisning

LORO-Balkonablauf mit Aufsatzelemente, Serie V-AK für Balkonabdichtung aus Flüssigkunststoffen im Wandbereich. Zweiteilige Ausführung für wärmeisolierte Balkone, mit aufgekanteten Klebeflansch für Einbau in Wand- oder Eckbereichen.

Nedlastinger



Alles online

[Monteringsanvisning \(PDF\)](#)

[Godkjenning \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[Måltegning \(PDF\)](#)

[Aufbauschema \(PDF\)](#)

[Brosjyre \(PDF\)](#)

[CAD 2D \(DXF\)](#)