


LORO-DJ FLAT ROOF DRAIN SIPHONIC FLOW 2-PART. CLAMMING FLANGE, VERTICAL, DN 100

LORO-DRAINJET stainless steel drain with two-part clamping flange without insulation DN 100

Описание

LORO-X DRAINLET flat roof siphonic drain, series 49(DJ), two-piece, without thermal insulation, vertical outlet, for main drainage with siphonic flow, discharge rate 27.0 l/s at 55 mm water level on the roof, with clamping flange as loose and fixed flange construction including compression seals, for bituminous and plastic roofing sheets, DRAINJET hood made of stainless steel, according to DIN EN 1253 with raised quality standard, proof of performance with standard-compliant testing system with 4.2 m non-ventilated downpipe according to LX data sheet LX530, made of stainless steel, DN100



Данни за артикула

ЕАН код	4038088072530
ЕТИМ клас	EC011398
Номинален диаметър	DN 100
Външни размери (ВxШxД)	300 x 300 x 423 mm
Тегло	7,50 Kg (STK)
Продуктова група	4
Митнически тарифен номер	73072980
Материал / Цвят	Edelstahl, Silber

Забележка за употреба

Große Dachflächen können durch leistungsstarke Systeme mit Druckströmung wirtschaftlich und sicher entwässert werden. LORO-X Schnellablaufsysteme mit Druckströmung werden durch die höhere Strömungsgeschwindigkeit mit kleineren Rohrdurchmessern bei gleichzeitig höherer Abflussleistung betrieben. Die hohe Strömungsgeschwindigkeit im Rohr erhöht darüber hinaus den Selbstreinigungseffekt. Einsatzgebiete Industriedächer, Gewerbe, Warmdächer, Kaldächer, Kastenrinnen, Tiefpunktlinien, Schnellablaufsysteme, große Dachflächen, Stadien, Lagerhallen, Logistikzentren.

Изтегляния



Alles online

[Инструкция за монтаж \(PDF\)](#)
[Сертификат \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[CAD чертеж \(PDF\)](#)
[Aufbauschema \(PDF\)](#)
[CAD \(DWG\)](#)

[Брошура \(PDF\)](#)
[Системен технически лист LX 530](#)