

LORO-DJ FLAT ROOF DRAIN SIPHONIC FLOW 2-PART. CLAMMING FLANGE, VERTICAL, DN 70

LORO-DRAINJET drain in stainless steel with two-part clamping flange with water insulation DN 70

Opis

LORO-X DRAINLET flat roof siphonic drain, series 49(DJ), one-piece, with thermal insulation, vertical outlet, for main drainage with siphonic flow, discharge rate 18.8 l/s at 55 mm water level on the roof, with clamping flange as loose and fixed flange construction including compression seals, for bituminous and plastic roofing sheets, DRAINJET hood made of stainless steel, according to DIN EN 1253 with raised quality standard, proof of performance with standard-compliant testing system with 4.2 m non-ventilated downpipe according to LX data sheet LX845, made of stainless steel, DN70




Podatki o izdelku

EAN koda	4038088069776
ETIM razred	EC011398
Nazivni premer	DN 70
Zunanje mere (VxŠxD)	260 x 260 x 413 mm
Teža	4,80 Kg (STK)
Skupina izdelkov	4
Carinska tarifna številka	73072980
Material / Barva	Edelstahl, Silber

Opomba za uporabo

Große Dachflächen können durch leistungsstarke Systeme mit Druckströmung wirtschaftlich und sicher entwässert werden. LORO-X Schnellablaufsysteme mit Druckströmung werden durch die höhere Strömungsgeschwindigkeit mit kleineren Rohrdurchmessern bei gleichzeitig höherer Abflussleistung betrieben. Die hohe Strömungsgeschwindigkeit im Rohr erhöht darüber hinaus den Selbstreinigungseffekt. Einsatzgebiete Industriedächer, Gewerbe, Warmdächer, Kaltdächer, Kastenrinnen, Tiefpunktlinien, Schnellablaufsysteme, große Dachflächen, Stadien, Lagerhallen, Logistikzentren.



Prenosi



Alles online

[Navodila za vgradnjo \(PDF\)](#)

[Certifikat \(PDF\)](#)

CAD 2D (DXF)

[Merska risba \(PDF\)](#)

[Aufbauschema \(PDF\)](#)

CAD (DWG)

[Prospekt \(PDF\)](#)

Podatkovni list sistema LX 845