


LORO-DJ EMERGENCY DRAIN SIPHONIC FLOW 1-PART. CLAMMING FLANGE, VERTICAL DN 100

LORO-DRAINJET stainless steel emergency drain with clamping flange, one-piece, without heat insulation DN 100

Описание

LORO-X DRAINLET flat roof siphonic drain, series 49(DJ), one-piece, without thermal insulation, vertical outlet, for emergency drainage with siphonic flow, discharge rate 38.0 l/s at 75 mm water level on the roof, with clamping flange as loose and fixed flange construction including compression seals, for bituminous and plastic roofing sheets, DRAINJET hood made of stainless steel, according to DIN EN 1253 with raised quality standard, proof of performance with standard-compliant testing system with 4.2 m non-ventilated downpipe according to LX data sheet LX542, made of stainless steel, DN100



Данни за артикула

ЕАН код	4038088072622
ЕТИМ клас	EC010827
Номинален диаметър	DN 100
Външни размери (ВxШxД)	300 x 300 x 386 mm
Тегло	3,90 Kg (STK)
Продуктова група	4
Митнически тарифен номер	73072980
Материал / Цвят	Edelstahl, Silber

Забележка за употреба

Große Dachflächen können durch leistungsstarke Systeme mit Druckströmung wirtschaftlich und sicher entwässert werden. LORO-X Schnellablaufsysteme mit Druckströmung werden durch die höhere Strömungsgeschwindigkeit mit kleineren Rohrdurchmessern bei gleichzeitig höherer Abflussleistung betrieben. Die hohe Strömungsgeschwindigkeit im Rohr erhöht darüber hinaus den Selbstreinigungseffekt. Einsatzgebiete Industriedächer, Gewerbe, Warmdächer, Kaldächer, Kastenrinnen, Tiefpunktlinien, Schnellablaufsysteme, große Dachflächen, Stadien, Lagerhallen, Logistikzentren.

Изтегляния



Alles online

[Инструкция за монтаж \(PDF\)](#)
[Сертификат \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[CAD чертеж \(PDF\)](#)
[Aufbauschema \(PDF\)](#)
[CAD \(DWG\)](#)

[Брошура \(PDF\)](#)
[Системен технически лист LX 542](#)