

LORO-DJ EMERGENCY DRAIN SIPHONIC FLOW 2-PART. CLAMMING FLANGE, VERTICAL, WITH THERMAL INSULATION AND HEATING DN 100

LORO-DRAINJET emergency drain in stainless steel with clamping flange, two-part with heat insulation and heater DN 100

Descrivere

LORO-X DRAINLET flat roof siphonic drain, series 49(DJ), two-piece, with thermal insulation and heating, vertical outlet, for emergency drainage with siphonic flow, discharge rate 38.0 l/s at 75 mm water level on the roof, with clamping flange as loose and fixed flange construction including compression seals, for bituminous and plastic roofing sheets, DRAINJET hood made of stainless steel, according to DIN EN 1253 with raised quality standard, proof of performance with standard-compliant testing system with 4.2 m non-ventilated downpipe according to LX data sheet LX542, made of stainless steel, DN100




Date articol

Cod EAN	4038088072677
Clasă ETIM	EC010827
Diametru nominal	DN 100
Dimensiuni exterioare (ÎxLxA)	300 x 300 x 423 mm
Greutate	8,10 Kg (STK)
Grupă de produse	4
Număr tarif vamal	73072980
Material / Culoare	Edelstahl, Silber

Notă de utilizare

Große Dachflächen können durch leistungsstarke Systeme mit Druckströmung wirtschaftlich und sicher entwässert werden. LORO-X Schnellablaufsysteme mit Druckströmung werden durch die höhere Strömungsgeschwindigkeit mit kleineren Rohrdurchmessern bei gleichzeitig höherer Abflussleistung betrieben. Die hohe Strömungsgeschwindigkeit im Rohr erhöht darüber hinaus den Selbstreinigungseffekt. Einsatzgebiete Industriedächer, Gewerbe, Warmdächer, Kaltdächer, Kastenrinnen, Tiefpunktlinien, Schnellablaufsysteme, große Dachflächen, Stadien, Lagerhallen, Logistikzentren.



Descărcări



Alles online

[Instrucțiuni de montaj \(PDF\)](#)

[Certificat \(PDF\)](#)

CAD 2D (DXF)

BIM 3D (IFC)

[Desen CAD \(PDF\)](#)

[Aufbauschema \(PDF\)](#)

CAD 3D (DWG)

[Broșură \(PDF\)](#)

Fisă tehnică de sistem LX 542

BIM 3D (STEP)