

LORO-DL SANIERUNGS ABL.EDELST.DN 100

LORO-DRAINLET stainless steel renovation drain DN 100

Description

LORO-X DRAINLET flat roof renovation drain, series 84(DL), one-piece, without thermal insulation, vertical outlet, for main drainage with gravity flow, discharge rate 6.5 l/s at 35 mm water level on the roof, with clamping flange as loose and fixed flange construction including compression seals, for bituminous and plastic roofing sheets, with transition sealing element for pipe inside diameter 118-130 mm, according to DIN EN 1253 with raised quality standard, proof of performance with standard-compliant testing system with 4.2 m non-ventilated downpipe, made of stainless steel, DN100




Article information

EAN Code	4038088090787
ETIM Class	EC011398
Nominal diameter	DN 100
Outside measurements (HxWxL)	300 x 300 x 516 mm
Weight	5,50 Kg (STK)
Product group	4
Customs tariff number	73072980
Material / Color	Edelstahl, Silber

Usage note

LORO-Flachdach-Sanierungsablauf mit Klebeflansch für Flüssigkunststoff DN 80 mit Übergangsdichtelement für Rohr-Innendurchmesser 98 - 106 mm



Downloads



Alles online

[Installation \(PDF\)](#)
[Certificate \(PDF\)](#)
[CAD drawing \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[Brochure \(PDF\)](#)
[CAD \(DWG\)](#)