

LORO-DL SANIERUNGS ABL.EDELST.DN 100

LORO-DRAINLET stainless steel renovation drain DN 100

Leírás

LORO-X DRAINLET flat roof renovation drain, series 84(DL), one-piece, without thermal insulation, vertical outlet, for main drainage with gravity flow, discharge rate 6.5 l/s at 35 mm water level on the roof, with clamping flange as loose and fixed flange construction including compression seals, for bituminous and plastic roofing sheets, with transition sealing element for pipe inside diameter 118-130 mm, according to DIN EN 1253 with raised quality standard, proof of performance with standard-compliant testing system with 4.2 m non-ventilated downpipe, made of stainless steel, DN100




Cikkadatok

EAN kód	4038088090787
ETIM osztály	EC011398
Névleges átmérő	DN 100
Külső méretek (MxSzxH)	300 x 300 x 516 mm
Súly	5,50 Kg (STK)
Termékcsoport	4
Vámtarifaszám	73072980
Anyag / Szín	Edelstahl, Silber

Használati megjegyzés

LORO-Flachdach-Sanierungsablauf mit Klebeflansch für Flüssigkunststoff DN 80 mit übergangs-Dichtelement für Rohr-Innendurchmesser 98 - 106 mm



Letöltések



Alles online

[Szerelési útmutató \(PDF\)](#)

[Engedély \(PDF\)](#)

[Méreterajz \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Prospektus \(PDF\)](#)

[CAD \(DWG\)](#)