

LORO-DL SANIERUNGS ABL.EDELST.DN 125

LORO-DRAINLET stainless steel renovation drain DN 125

Descripción

LORO-X DRAINLET flat roof renovation drain, series 84(DL), one-piece, without thermal insulation, vertical outlet, for main drainage with gravity flow, discharge rate 9.8 l/s at 45 mm water level on the roof, with clamping flange as loose and fixed flange construction including compression seals, for bituminous and plastic roofing sheets, with transition sealing element for pipe inside diameter 145-155 mm, according to DIN EN 1253 with raised quality standard, proof of performance with standard-compliant testing system with 4.2 m non-ventilated downpipe, made of stainless steel, DN125




Datos del artículo

Código EAN	4038088090794
Clase ETIM	EC011398
Diámetro nominal	DN 125
Medidas exteriores (AxAxL)	330 x 330 x 516 mm
Peso	5,50 Kg (STK)
Grupo de productos	4
Número de arancel aduanero	73072980
Material / Color	Edelstahl, Silber

Nota de uso

LORO-Flachdach-Sanierungsablauf mit Klebeflansch für Flüssigkunststoff DN 80 mit Übergangs-Dichtelement für Rohr-Innendurchmesser 98 - 106 mm



Descargas



Alles online

[Instrucciones de instalación \(PDF\)](#)
[Certificado \(PDF\)](#)

[Dibujo dimensional \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Folleto \(PDF\)](#)
[CAD \(DWG\)](#)