


LORO-DL FLAT ROOF DRAIN MAIN-GRAVITY FLOW 2-PART. CLAMMING FLANGE, VERTICAL WITH THERMAL INSULATION AND HEATING DN 100

LORO-DRAINLET drain in stainless steel with clamping flange vertical two-part with heat insulation and heating DN 100

Περιγραφή

LORO-X DRAINLET flat roof drain, series 84(DL), two-piece, with thermal insulation and heating, vertical outlet, for main drainage with gravity flow, discharge rate 6,5 l/s at 35 mm water level on the roof, with clamping flange as loose and fixed flange construction including compression seals, for bituminous and plastic roofing sheets, DRAINLET hood made of stainless steel, according to DIN EN 1253 with raised quality standard, proof of performance with standard-compliant testing system with 4.2 m non-ventilated downpipe according to LX data sheet LX873, made of stainless steel, DN100



Στοιχεία προϊόντος

Κωδικός EAN 4038088073278

Κατηγορία ETIM EC011398

Ονομαστική διάμετρος DN 100

Εξωτερικές διαστάσεις (ΥxΠxΜ) 300 x 300 x 423 mm

Βάρος 7,80 Kg (STK)

Ομάδα προϊόντων 4

Δασμολογικός αριθμός 73072980

Υλικό / Χρώμα Edelstahl, Silber

Σημείωση χρήσης

Platzsparende Maße ohne „Topf“ in der Dachfläche und ein hoher Abfluss durch die leistungsstarke LORO-X Haube mit Belüftungsöffnungen zeichnen die LORO-X DRAINLET® Hauptentwässerung und Notentwässerung mit Freispiegelströmung aus. Der Klemmflansch als Los- und Festflanschkonstruktion ist für Abdichtungsbahnen (Ablauf) und Dampfsperren (2-teilig) aus Bitumen und Kunststoff gleichermaßen geeignet. Einsatzgebiete Flachdächer, Warmdächer, Kaldächer, befahrbare Dachflächen, Umkehrdächer, Gründächer, Abdichtungsbahnen aus Bitumen und Kunststoff, Trapezblechdächer, Kastenrinnen.

Λήψεις



Alles online

[Οδηγίες εγκατάστασης \(PDF\)](#)

[Έγκριση \(PDF\)](#)

[Φύλλο δεδομένων συστήματος LX](#)

[4093D \(STEP\)](#)

[Σχέδιο διαστάσεων \(PDF\)](#)

[Aufbauschema \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Φυλλάδιο \(PDF\)](#)

[Φύλλο δεδομένων συστήματος LX](#)

[873D 3D \(DWG\)](#)

[BIM Revit \(RFA\)](#)