Fiche technique du produit

LORO_Produkt-Datenblatt_21523.125X_fr.pdf
Article 21523.125X
29.11.2026, 20:41 h


LORO-DL FLAT ROOF DRAIN MAIN-GRAVITY FLOW 2-PART. CLAMBING FLANGE, VERTICAL WITH THERMAL INSULATION AND HEATING DN 125

LORO-DRAINLET drain in stainless steel with clamping flange, vertical, two-part, with heat insulation and heating DN 125

Texte de prescription

LORO-X DRAINLET flat roof drain, series 84(DL), two-piece, with thermal insulation and heating, vertical outlet, for main drainage with gravity flow, discharge rate 9.8 l/s at 45 mm water level on the roof, with clamping flange as loose and fixed flange construction including compression seals, for bituminous and plastic roofing sheets, DRAINLET hood made of stainless steel, according to DIN EN 1253 with raised quality standard, proof of performance with standard-compliant testing system with 4.2 m non-ventilated downpipe according to LX data sheet LX874, made of stainless steel, DN125





Données de l'article

Code EAN	**4038088073520**
Classe ETIM	**EC011398**
Diamètre nominal	**DN 125**
Dimensions extérieures (HxLxP)	**330 x 330 x 432 mm**
Poids	**9,80 Kg (STK)**
Groupe de produits	**4**
Numéro tarifaire douanier	**73072980**
Matériau / Couleur	**Edelstahl, Silber**

Note d'utilisation

Platzsparende Maße ohne „Topf“ in der Dachfläche und ein hoher Abfluss durch die leistungsstarke LORO-X Haube mit Belüftungsöffnungen zeichnen die LORO-X DRAINLET® Hauptentwässerung und Notentwässerung mit Freispiegelströmung aus. Der Klemmflansch als Los- und Festflanschkonstruktion ist für Abdichtungsbahnen (Ablauf) und Dampfsperren (2-teilig) aus Bitumen und Kunststoff gleichermaßen geeignet. Einsatzgebiete Flachdächer, Warmdächer, Kaltdächer, befahrbare Dachflächen, Umkehrdächer, Gründächer, Abdichtungsbahnen aus Bitumen und Kunststoff, Trapezblechdächer, Kastenrinnen.

Téléchargements

Alles online

Notice d'installation (PDF)
Certificat (PDF)
CAD 2D (DXF)
Dessin dimensionnel (PDF)
Aufbauschema (PDF)
CAD (DWG)
Brochure (PDF)
Fiche technique du système LX 874
BIM Revit (RFA)