


LORO-DL HPT.ABL.KLEMMFL.SENKR.1-TLG.O.WD

LORO-DRAINLET main drain clamping flange vertical one-piece without insulation with retention pipe according to specification

Περιγραφή

LORO-X DRAINLET flat roof drain for overload-free main drainage, please contact LOROWERK for the determination of the necessary retention openings for the main drainage and variable-height retention pipe, series 84(DL) one piece without thermal insulation, vertical pipe, for main drainage with gravity flow, discharge rate max. 4.5 l/s with a water height of up to 75 mm on the roof, with clamping flange as loose and fixed flange construction, for bitumen and plastic roofing sheets, DRAINLET hood made of stainless steel, according to DIN EN 1253, proof of performance according to LX-specification sheet LX1871, made of stainless steel, DN100



Στοιχεία προϊόντος

Κωδικός EAN	4038088100394
Κατηγορία ETIM	EC011398
Ονομαστική διάμετρος	DN 100
Εξωτερικές διαστάσεις (ΥxΠxΜ)	390 x 300 x 300 mm
Βάρος	4,80 Kg (STK)
Ομάδα προϊόντων	9
Δασμολογικός αριθμός	73072980
Υλικό / Χρώμα	Edelstahl, Silber

Σημείωση χρήσης

kein Verwendungshinweis notwendig

