

LORO-ABZWEIG QUADRATISCH DN II=LX-MUFFE

LORO-X branch square DN II=LX socket

Beskrivelse

LORO-X branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, building material class A1, dimensionally stable, break-proof, square/round, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 87 degrees, DN70




Artikkeldata

EAN-kode	4038088024188
ETIM-klasse	EC003025
Nominell diameter	DN 70, DN 70
Nominell lengde/grad	87
Utvendige mål (HxBxL)	76 x 155 x 220 mm
Vekt	1,40 Kg (STK)
Produktgruppe	1
Tolltariffnummer	73089098
Materiale / Farge	Stahl feuerverzinkt, Silber

Bruksanvisning

LORO-X Abzweige quadratisch/rund eignen sich zum seitlichen Einleiten von runden LORO-X Röhren z.B. von Balkonen in eine quadratische LORO-X Fallleitung.



Nedlastinger



Alles online

[Monteringsanvisning \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Måltegning \(PDF\)](#)

[CAD \(DWG\)](#)

[Brosjyre \(PDF\)](#)

[BIM IFC4 \(parametrisk\)](#)