LORO-X COMPOSITE PIPE WITH 1 SOCKET 150 MM DN 50

LORO multilayer pipe 150 mm DN 50

Description

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 150 mm long, DN50



Article information

EAN Code	**4038088044537**
ETIM Class	**EC010225**
Nominal diameter	**DN 50**
Nominal length/degree	**150**
Outside measurements (HxWxL)	**89 x 89 x 188 mm**
Weight	**1,10 Kg (STK)**
Product group	**3**
Customs tariff number	**73063012**
Material / Color	**Stahl feuerverzinkt, Silber**

Usage note

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Däammschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Downloads

Installation (PDF)
CAD drawing (PDF)
Brochure (PDF)
CAD 2D (DXF)
CAD (DWG)

Alles online