


LORO-X COMPOSITE PIPE WITH 1 SOCKET

150 MM DN 70

LORO multilayer pipe 150 mm DN 70

Popis

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 150 mm long, DN70



Údaje o artikli

EAN kód	4038088038222
ETIM trieda	EC010225
Menovitý priemer	DN 70
Menovitá dĺžka/stupeň	150
Vonkajšie rozmery (VxŠxH)	102 x 102 x 205 mm
Hmotnosť	1,10 Kg (STK)
Skupina produktov	3
Colný sadzovník	73063012
Materiál / Farba	Stahl feuerverzinkt, Silber

Pokyny na použitie

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Na stiahnutie



Alles online

[Návod na montáž \(PDF\)](#)

CAD 2D (DXF)

[Rozmerový výkres \(PDF\)](#)

CAD (DWG)

[Prospekt \(PDF\)](#)