

LORO-X COMPOSITE PIPE WITH 1 SOCKET 3000 MM DN 40

LORO-Composite Pipe 3000 mm DN 40

Beskrivning

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 3000 mm long, DN40




Artikeldata

EAN-kod	4038088049426
ETIM-klass	EC010225
Nominell diameter	DN 40
Nominell längd/grad	3000
Yttermått (HxBxL)	89 x 89 x 3030 mm
Vikt	15,00 Kg (STK)
Produktgrupp	3
Tullnummer	73063012
Material / Färg	Stahl feuerverzinkt, Silber

Användningsanvisning

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Nedladdningar



Alles online

[Monteringsanvisning \(PDF\)](#)
[Måttitning \(PDF\)](#)
[Broschyr \(PDF\)](#)