

LORO-X COMPOSITE PIPE WITH 1 SOCKET

3000 MM DN 80

LORO multilayer pipe 3000 mm DN 80

Описание

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 3000 mm long, DN 80




Данни за артикула

ЕАН код	4038088049433
ЕТИМ клас	EC010225
Номинален диаметър	DN 80
Номинална дължина/градус	3000
Външни размери (ВxШxД)	133 x 133 x 3060 mm
Тегло	40,00 Kg (STK)
Продуктова група	3
Митнически тарифен номер	73063012
Материал / Цвят	Stahl feuerverzinkt, Silber

Забележка за употреба

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Изтегляния



Alles online

[Инструкция за монтаж \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[CAD чертеж \(PDF\)](#)

[CAD \(DWG\)](#)

[Брошура \(PDF\)](#)