

LORO-X COMPOSITE PIPE WITH 1 SOCKET

3000 MM DN 150

LORO-Composite Pipe 3000 mm DN 150

Descrição

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 3000 mm long, DN150




Dados do artigo

Código EAN	4038088024447
Classe ETIM	EC010225
Diâmetro nominal	DN 150
Comprimento/grau nominal	3000
Medidas exteriores (AxLxP)	219 x 219 x 3080 mm
Peso	86,00 Kg (STK)
Grupo de produtos	3
Número de pauta aduaneira	73063018
Material / Cor	Stahl feuerverzinkt, Silber

Nota de utilização

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Transferências



Alles online

[Instruções de instalação \(PDF\)](#)
[Desenho cotado \(PDF\)](#)
[Brochura \(PDF\)](#)