LORO-X COMPOSITE PIPE WITH 1 SOCKET 2000 MM DN 32

LORO-Composite Pipe 2000 mm DN 32

Tekst za troškovnik

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 2000 mm long, DN32



Podaci o artiklu

EAN kod	**4038088086384**
ETIM klasa	**EC010225**
Nazivni promjer	**DN 32**
Nazivna duljina/stupanj	**2000**
Vanjske mjere (VxŠxD)	**89 x 89 x 2025 mm**
Težina	**8,90 Kg (STK)**
Grupa proizvoda	**3**
Carinski tarifni broj	**73063012**
Materijal / Boja	**Stahl feuerverzinkt, Silber**

Napomena za upotrebu

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Däammschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Preuzimanja

Alles online

Upute za ugradnju (PDF)
CAD 2D (DXF)
Dimenzijski crtež (PDF)
CAD (DWG)
Prospekt (PDF)