


LORO-X COMPOSITE PIPE WITH 1 SOCKET

2000 MM DN 32

LORO-Composite Pipe 2000 mm DN 32

Texto para caderno de encargos

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 2000 mm long, DN32



Dados do artigo

Código EAN	4038088086384
Classe ETIM	EC010225
Diâmetro nominal	DN 32
Comprimento/grau nominal	2000
Medidas exteriores (AxLxP)	89 x 89 x 2025 mm
Peso	8,90 Kg (STK)
Grupo de produtos	3
Número de pauta aduaneira	73063012
Material / Cor	Stahl feuerverzinkt, Silber

Nota de utilização

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Transferências



Alles online

[Instruções de instalação \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Desenho cotado \(PDF\)](#)
[CAD \(DWG\)](#)

[Brochura \(PDF\)](#)