


LORO-X COMPOSITE PIPE WITH 1 SOCKET

2000 MM DN 32

LORO-Composite Pipe 2000 mm DN 32

Voce di capitolato

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 2000 mm long, DN32



Dati articolo

Codice EAN 4038088086384

Classe ETIM EC010225

Diametro nominale DN 32

Lunghezza/grado nominale 2000

Misure esterne (AxLxP) 89 x 89 x 2025 mm

Peso 8,90 Kg (STK)

Gruppo prodotti 3

Numero tariffa doganale 73063012

Materiale / Colore Stahl feuerverzinkt, Silber

Note d'uso

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Download



Alles online

[Istruzioni di installazione \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Disegno dimensionale \(PDF\)](#)
[CAD \(DWG\)](#)

[Brochure \(PDF\)](#)