

## LORO-X COMPOSITE PIPE WITH 1 SOCKET 2000 MM DN 80

### LORO-Composite Pipe 2000 mm DN 80

#### Descrição

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 2000 mm long, DN 80




#### Dados do artigo

|                            |                             |
|----------------------------|-----------------------------|
| Código EAN                 | 4038088049471               |
| Classe ETIM                | EC010225                    |
| Diâmetro nominal           | DN 80                       |
| Comprimento/grau nominal   | 2000                        |
| Medidas exteriores (AxLxP) | 133 x 133 x 2060 mm         |
| Peso                       | 26,00 Kg (STK)              |
| Grupo de produtos          | 3                           |
| Número de pauta aduaneira  | 73063012                    |
| Material / Cor             | Stahl feuerverzinkt, Silber |

#### Nota de utilização

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



#### Transferências



Alles online

[Instruções de instalação \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Desenho cotado \(PDF\)](#)

[CAD \(DWG\)](#)

[Brochura \(PDF\)](#)