

## LORO-X COMPOSITE PIPE WITH 1 SOCKET 1000 MM DN 100

### LORO-Composite Pipe 1000 mm DN 100

#### Beschrijving

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 1000 mm long, DN100




#### Artikelgegevens

|                          |                             |
|--------------------------|-----------------------------|
| EAN-code                 | 4038088024522               |
| ETIM Klasse              | EC010225                    |
| Nominale diameter        | DN 100                      |
| Nominale lengte/graad    | 1000                        |
| Buitenafmetingen (HxBxL) | 133 x 133 x 1070 mm         |
| Gewicht                  | 15,00 Kg (STK)              |
| Productgroep             | 3                           |
| Douanetariefnumme        | 73063012                    |
| r                        |                             |
| Materiaal / Kleur        | Stahl feuerverzinkt, Silber |

#### Gebruiksaanwijzing

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



#### Downloads



Alles online

[Installatiehandleiding \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[Maattekening \(PDF\)](#)
[CAD \(DWG\)](#)
[Brochure \(PDF\)](#)