LORO-X COMPOSITE PIPE WITH 1 SOCKET 500 MM DN 32

LORO-Composite Pipe 1 socket 500 mm DN 32

Kiírási szöveg

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 500 mm long, DN32



Cikkadatok

EAN kód	**4038088067833**
ETIM osztály	**EC010225**
Névleges átmérő	**DN 32**
Névleges hossz/fok	**500**
Külső méretek (MxSzxH)	**89 x 89 x 525 mm**
Súly	**2,50 Kg (STK)**
Termékcsoport	**3**
Vámtarifaszám	**73063012**
Anyag / Szín	**Stahl feuerverzinkt, Silber**

Használati megjegyzés

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Däammschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Letöltések

Alles online

Szerelési útmutató (PDF)
Méretrajz (PDF)
Prospektus (PDF)
CAD 2D (DXF)
CAD (DWG)
BIM IFC4 (parametrisch)