

## LORO-X COMPOSITE PIPE WITH 1 SOCKET 500 MM DN 100

LORO multilayer pipe 500 mm DN 100

### Beskrivning

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 500 mm long, DN100




### Artikeldata

|                     |                             |
|---------------------|-----------------------------|
| EAN-kod             | 4038088024577               |
| ETIM-klass          | EC010225                    |
| Nominell diameter   | DN 100                      |
| Nominell längd/grad | 500                         |
| Yttermått (HxBxL)   | 133 x 133 x 570 mm          |
| Vikt                | 8,00 Kg (STK)               |
| Produktgrupp        | 3                           |
| Tullnummer          | 73063012                    |
| Material / Färg     | Stahl feuerverzinkt, Silber |

### Användningsanvisning

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



### Nedladdningar



Alles online

[Monteringsanvisning \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Måttitning \(PDF\)](#)

[CAD \(DWG\)](#)

[Broschyr \(PDF\)](#)