

LORO-X COMPOSITE PIPE WITH 1 SOCKET 500 MM DN 125

LORO multilayer pipe 500 mm DN 125

Kuvaus

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 500 mm long, DN125




Tuotetiedot

EAN-koodi	4038088024584
ETIM-luokka	EC010225
Nimellishalkaisija	DN 125
Nimellispituus/-aste	500
Ulkomitat (KxLxS)	168 x 168 x 575 mm
Paino	11,20 Kg (STK)
Tuoteryhmä	3
Tullitariffin numero	73063018
Materiaali / Väri	Stahl feuerverzinkt, Silber

Käyttöohje

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Lataukset



Alles online

[Asennusohje \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Mittapiirustus \(PDF\)](#)

[CAD \(DWG\)](#)

[Esite \(PDF\)](#)