LORO-X COMPOSITE PIPE WITH 1 SOCKET 500 MM DN 200

LORO-Composite pipe + 1 socket

Description

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 500 mm long, DN200

Article information

EAN Code	4038088036235
ETIM Class	EC010225
Nominal diameter	DN 200
Nominal length/degree	500
Outside measurements (HxWxL)	273 x 273 x 370 mm
Weight	22,70 Kg (STK)
Product group	3
Customs tariff number	73063018
Material / Color	Stahl feuerverzinkt, Silber

Usage note

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Däammschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Downloads

Installation (PDF) Brochure (PDF) BIM IFC4 (parametrisch)

Alles online