

## LORO-X COMPOSITE PIPE WITH 1 SOCKET 250 MM DN 32

### LORO-Composite Pipe 1 socket 250 mm DN 32

#### Bestektekst

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 250 mm long, DN32




#### Artikelgegevens

|                          |                             |
|--------------------------|-----------------------------|
| EAN-code                 | 4038088067840               |
| ETIM Klasse              | EC010225                    |
| Nominale diameter        | DN 32                       |
| Nominale lengte/graad    | 250                         |
| Buitenafmetingen (HxBxL) | 89 x 89 x 275 mm            |
| Gewicht                  | 1,40 Kg (STK)               |
| Productgroep             | 3                           |
| Douanetariefnumme        | 73063012                    |
| r                        |                             |
| Materiaal / Kleur        | Stahl feuerverzinkt, Silber |

#### Gebruiksaanwijzing

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



#### Downloads



Alles online

[Installatiehandleiding \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[Maattekening \(PDF\)](#)
[CAD \(DWG\)](#)
[Brochure \(PDF\)](#)
[BIM IFC4 \(parametrisch\)](#)