

LORO-X COMPOSITE PIPE WITH 1 SOCKET 250 MM DN 40

LORO-Composite Pipe 250 mm DN 40

Description

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 250 mm long, DN40




Article information

EAN Code	4038088049563
ETIM Class	EC010225
Nominal diameter	DN 40
Nominal length/degree	250
Outside measurements (HxWxL)	89 x 89 x 280 mm
Weight	1,40 Kg (STK)
Product group	3
Customs tariff number	73063012
Material / Color	Stahl feuerverzinkt, Silber

Usage note

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Downloads



Alles online

[Installation \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[CAD drawing \(PDF\)](#)
[CAD \(DWG\)](#)
[Brochure \(PDF\)](#)