

LORO-X COMPOSITE PIPE WITH 1 SOCKET 250 MM DN 70

LORO multilayer pipe 250 mm DN 70

Beskrivelse

LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 250 mm long, DN70




Artikeldata

EAN-kode	4038088024614
ETIM Klasse	EC010225
Nominal diameter	DN 70
Nominal længde/grad	250
Ydermål (HxBxL)	102 x 102 x 305 mm
Vægt	2,30 Kg (STK)
Produktgruppe	3
Toldtarifnummer	73063012
Materiale / Farve	Stahl feuerverzinkt, Silber

Brugsanvisning

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Downloads



Alles online

[Installationsvejledning \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Måltegning \(PDF\)](#)

[CAD \(DWG\)](#)

[Brochure \(PDF\)](#)