

LORO-X COMPOSITE PIPE WITH 1 SOCKET 1500 MM DN 32

LORO-Composite Pipe 1.500 mm DN 32

Tekst za troškovnik


LORO-X compound pipe consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC free) and outer pipe (LORO-X pipe, made of steel, hot-dip galvanized), 1500 mm long, DN32

Podaci o artiklu

EAN kod	4038088067802
ETIM klasa	EC010225
Nazivni promjer	DN 32
Nazivna duljina/stupanj	1500
Vanjske mjere (VxŠxD)	89 x 89 x 1525 mm
Težina	7,50 Kg (STK)
Grupa proizvoda	3
Carinski tarifni broj	73063012
Materijal / Boja	Stahl feuerverzinkt, Silber

Napomena za upotrebu

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Preuzimanja



Alles online

[Upute za ugradnju \(PDF\)](#)

CAD 2D (DXF)

[Dimenzijski crtež \(PDF\)](#)

CAD (DWG)

[Prospekt \(PDF\)](#)